

CXH5-1

桅顶灯

CXH17/CXH19

信号灯

CXH5-1

Mast Head Light

CXH17/CXH19

Signal Light



CXH5-1



CXH17



CXH19

应用场所 Application

- 适用于船舶作昼夜航行灯光信号。
- Suitable for day and night navigation signal of ships.
- 适用于长度≥50米船舶作夜间航行之用。
- Suitable for night navigation of ships whose length is 50 meters or above.

型号含义 Catalogue number logic



灯体 Housing

- CXH5-1 : 黄铜材质, 表面喷塑
- CXH5-1: Brass material, powder coated surface
- CXH17 : 不锈钢
- CXH17: Stainless steel
- CXH19 : 铜
- CXH19: Copper

透明罩 Transparent cover

- 聚碳酸酯(PC材质)
- PC material

选配表 Selection table

● 绿 Green ● 红 Red ○ 白色 White ● 黄 Yellow ● 蓝 Blue ● 紫 Purple

型号 Type	规格 Specification	光源类型 Light source	可见距离 Visibility	水平光弧 Level arc	颜色 Color	壳体类型 Enclosure	重量(kg) Weight
CXH5-1	220V/230V LED 5W 110V LED 5W	LED 灯泡 LED lamp	3n.m	360°	● ● ● ○ ● ●	I	1.5
CXH17					● ● ○ ●	II	1.1
CXH19					○ ● ● ● ●	/	1.4
					○ ● ● ● ●	/	0.8

技术参数 Technical parameters

执行标准 Conformity to standards	IEC 60598 , CCS 入级规范 (CCS standard)
环境温度 Ambient temperature	-40°C~+55°C
防护等级 Degree of protection	IP56
光源类型 Light source	LED 灯泡 LED lamp
灯座 Lamp holder	E27
电缆入口 Cable entris	CXH5-1 : G3/4"通头, 适用于Φ9~Φ11mm电缆 CXH5-1: G3/4" gland nut, suitable for Φ9~Φ11mm cable
	CXH17、CXH19 : 适用于Φ10~Φ14mm电缆 CXH17, CXH19: suitable for Φ10~Φ14mm cable

外形尺寸 Outline dimension

