


Accessories

Selection table of BPS(H) explosion-proof drain plug (Breather)

<p>BPS(H)-I</p> 	<p>Explosion protection</p> <p>Global (IECEX) IECEx CQM 22.0023X Gas and dust Ex db IIC T6/T5/96°C (T4) Gb Ex tb IIIC T80°C/T95°C/T130°C Db</p> <p>Europe (ATEX) TÜV CY 23 ATEX 0206872U Gas and dust Ex II 2 G Ex db IIC T6/T5/96°C (T4) Gb Ex II 2 D Ex tb IIIC T80°C/T95°C/T130°C Db</p> <p>Certificates IECEx; ATEX; CU-TR</p> <p>Conformity to standards EN 60079-0, EN 60079-1, EN 60079-31 IEC 60079-0, IEC 60079-1, IEC 60079-31</p> <p>Material SS316 (SS304, SS316L is optional)</p> <p>Thread specification M20×1.5</p> <p>Degree of protection IP66</p> <p>Ambient temperature T6 for Tamb: -60°C~+44°C T5 for Tamb: -60°C~+59°C 96°C(T4) for Tamb: -60°C~+60°C</p>
<p>BPS(H)-II</p> 	<p>Explosion protection</p> <p>Global (IECEX) IECEx CQM 22.0023X Gas and dust Ex eb IIC T6...T4 Gb Ex tb IIIC T80°C/T95°C/T130°C Db</p> <p>Europe (ATEX) TÜV CY 23 ATEX 0206872U Gas and dust Ex II 2 G Ex eb IIC T6...T4 Gb Ex II 2 D Ex tb IIIC T80°C/T95°C/T130°C Db</p> <p>Certificates IECEx; ATEX; CU-TR</p> <p>Conformity to standards EN 60079-0, EN 60079-7, EN 60079-31 IEC 60079-0, IEC 60079-7, IEC 60079-31</p> <p>Material Brass (SS304, SS316, SS316L is optional)</p> <p>Thread specification M20×1.5</p> <p>Degree of protection IP66</p> <p>Ambient temperature T6/T80°C for Tamb: -60°C~+80°C T5/T95°C for Tamb: -60°C~+95°C T4/T130°C for Tamb: -60°C~+130°C</p>



Selection table of cable clamp

Version	Size Code	Dimensions (mm)			Applicable cable outer diameter (Φ)	For DQM-I/II, DQM-I/III DQM-II/III, DQM-III/I DQM-III/II, DQM-CF	Hexagon socket	Ordering code	Weight (kg)
		B	L	G					
	A	25	76	37.5	5.5~16	M20A M20B M25A	#3	722001	0.026
	B	30	88	43	12.5~20.5	M20C M25B M32A	#4	722002	0.045
	C	38	88	53	17~26	M25C M32B M40A	#4	722003	0.047
	D	45	95	60	22~33	M32C M40B M50A	#4	722004	0.056
	E	56	95	71	28~41	M40C M50B M63A	#4	722005	0.057
<p>Material: Stainless steel</p> <p>Function: For DQM Series Explosion-proof Cable Glands, providing additional anti-pulling measures.</p> <p>Note: Dimensions B and G are available for customization.</p>									