



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:	IECEX CQM 22.0002X	Page 1 of 4	<u>Certificate history:</u>
Status:	Current	Issue No: 5	Issue 4 (2025-11-12)
Date of Issue:	2026-04-27		Issue 3 (2025-02-15)
Applicant:	WAROM TECHNOLOGY INCORPORATED COMPANY No. 555 Baoqian Road, Jiading District, Shanghai, 201808 China		Issue 2 (2023-09-05)
Equipment:	Explosion-proof Distribution Panel typed BXM(D)8061		Issue 1 (2022-10-31)
Optional accessory:			Issue 0 (2022-05-20)
Type of Protection:	Flameproof enclosure "db", Increased safety "eb", Encapsulation "mb", Dust ignition protection by enclosure "tb"		
Marking:	Ex db eb mb II C T3/T4/T5/T6 Gb		
	Ex tb IIIC T80°C Db		

Approved for issue on behalf of the IECEx
Certification Body:

Ji Xiaodong

Position:

President

Signature:
(for printed version)

Date:
(for printed version)

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

China Quality Mark Certification Group Co., Ltd.
No. 33 Zengguang Road, Haidian District
Beijing City, Postal code: 100048
China





IECEX Certificate of Conformity

Certificate No.: **IECEX CQM 22.0002X**

Page 2 of 4

Date of issue: 2026-04-27

Issue No: 5

Manufacturer: **WAROM TECHNOLOGY INCORPORATED COMPANY**
No. 555 Baoqian Road, Jiading District, Shanghai, 201808
China

Manufacturing locations: **WAROM TECHNOLOGY INCORPORATED COMPANY**
No. 555 Baoqian Road, Jiading District, Shanghai, 201808
China

WAROM TECHNOLOGY MENA FZCO
Plot, S10103,
Jebal Ali South,
Jebal Ali Freezone
DUBAI PO Box: 263667
United Arab Emirates

WAROM TECHNOLOGY ARABIA INDUSTRIAL LLC
Building No. 4443, Ibn Sina Street, 1st Industrial District
Dammam 32234
Saudi Arabia

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

[IEC 60079-0:2017](#) Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

[IEC 60079-1:2014](#) Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
Edition:7.0

[IEC 60079-18:2017](#) Explosive atmospheres - Part 18: Protection by encapsulation "m"
Edition:4.1

[IEC 60079-31:2022](#) Explosive atmospheres – Part 31: Equipment dust ignition protection by enclosure "t"
Edition:3.0

[IEC 60079-7:2017](#) Explosive atmospheres - Part 7: Equipment protection by increased safety "e"
Edition:5.1

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

[CN/CQM/ExTR22.0013/00](#)
[CN/CQM/ExTR22.0013/03](#)

[CN/CQM/ExTR22.0013/01](#)
[CN/CQM/ExTR22.0013/04](#)

[CN/CQM/ExTR22.0013/02](#)

Quality Assessment Report:

[CN/CQM/QAR07.0003/15](#)



IECEx Certificate of Conformity

Certificate No.: **IECEx CQM 22.0002X**

Page 3 of 4

Date of issue: 2026-04-27

Issue No: 5

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

BXM (D) 8061 explosion-proof distribution panel is suitable for hazardous area up to Group IIC and Group IIIC, Zone 1, Zone 2, Zone 21 and Zone 22. The temperature classes of the equipment vary from T3/T80°C to T6/T80°C based on different configurations of installed components.

The material of the enclosure is available in Q235, 304 or 316L, which has excellent properties such as corrosion resistance, impact resistance and good thermal stability.

The distribution panel adopts modular design as a whole, and various circuits can be freely combined via copper bars and terminals. The surface mounting elements include the operating handle of the circuit breaker, universal switch, plug and socket. Separate certified Ex components or equipment in the enclosure include circuit breakers, terminals, temperature switch, heaters, indicator, button, switch, fuse and instrument. Under the condition of not exceeding the highest power consumption, the enclosure can also be equipped with aluminum alloy IIC explosion-proof box, which can be equipped with molded case circuit breakers, miniature circuit breakers, intermediate relays, time relays, surge protectors, fuses, AC contactors, thermal relays, transformers, Insulation Monitoring Devices (IMD) and Earth Fault Indicators (EFI), programmable logic controllers, power modules and other non-explosion-proof electrical components.

The ingress protection of enclosure is IP66 in according with IEC 60529.

Refer to attachment for the detail of Ex marking, ratings and components used.

SPECIFIC CONDITIONS OF USE: YES as shown below:

1. When the ambient temperature is -20°C/-40°C~ +40°C, it is suitable for the temperature group T5/T80°C, when the ambient temperature is -20°C/-40°C~ +55°C, it is suitable for temperature group T4/T80°C; The ambient temperature is -20°C/-40°C~ +45°C, it is suitable for temperature group T4/T80°C with structured specified in drawing "615690070001".
2. When the ambient temperature is -20°C/-40°C~ +55°C, main switch current Max.25A, it is suitable for the temperature group T6/T80°C refer to the drawing "615690108801, 615690109001 and 615690109101".
3. When the product is installed in explosive gas atmosphere, separate certified cable glands or blanking elements fulfil requirements of IEC 60079-0:2017 and IEC 60079-7:2015 with Ex marking Ex eb IIC Gb, IP66 shall be incorporated.
4. When the product is installed in combustible dust atmosphere, separate certified cable glands or blanking elements fulfil requirements of IEC 60079-0:2017 and IEC 60079-31:2022 with Ex marking Ex tb IIIC Gb, IP66 shall be incorporated.
5. Use screws with yield strength $\geq 450\text{MPa}$ for Ex db breaker in the product.
6. Observe the WARNING: "DO NOT OPEN WHEN ENERGIZED!" and "DO NOT OPEN WHEN COMBUSTIBLE DUST ATMOSPHERE MAY BE PRESENT"; When plug and socket are connected, WARNING: "DO NOT DISCONNECT WHEN ENERGIZED!" .



IECEX Certificate of Conformity

Certificate No.: **IECEX CQM 22.0002X**

Page 4 of 4

Date of issue: 2026-04-27

Issue No: 5

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

- 1.Update the instruction manual.
- 2.Added new structure scheme for T6/T80°C..
- 3.Added new structure scheme with ambient temperature is -20°C/-40°C~+40°C/+45°C/+55°C..
- 4.Add new options of increased safety terminals.
- 5.Add new options of electrical heaters and change related Ex marking.
- 6.Add new type of breaker.
- 7.Update the information of Ex components according to their latest certificates.
- 8.Assembly drawing has been updated accordingly.
- 9.Update the specific condition of use accordingly.

Annex:

[IECEX_CQM_22.0002X_005 attachmnet.pdf](#)



Attachment to CoC

IECEX CQM 22.0002X issue 5

**Manufacturer:**

WAROM TECHNOLOGY INCORPORATED COMPANY

Address: No. 555 Baoqian Road, Jiading District, Shanghai, 201808, China

Electrical equipment:

Explosion-proof Distribution Panel typed BXM(D)8061

Ratings:

Max. AC 690V 50/60Hz, Max. DC 500V

Max. 250A (Main switch current)

Ex marking:

When the product is without heater, the marking is:

Ex db eb mb IIC T6 Gb (Ta: -20°C/-40°C~+55°C, Max. 25A)

Ex db eb mb IIC T5 Gb (Ta: -20°C/-40°C~+40°C,Max. 250A)

Ex db eb mb IIC T4 Gb (Ta: -20°C/-40°C~+55°C,Max. 250A)

Ex tb IIIC T80°C Db (Ta: -20°C/-40°C~ +40°C/+55°C)

When the product is equipped with an explosion-proof heater, the marking is:

Ex db eb mb IIC T4 Gb (Ta: -20°C/-40°C~+45°C, Max. 250A)

(With heater:CREx02041.0-XX,CREx02042.0-XX,CREx02051.0-XX,CREx02052.0-XX)

Ex db eb mb IIC T4 Gb (Ta: -20°C/-40°C~+55°C, Max. 250A)

(With heater: 27-2C54-7054/110Z/5000, 27-2B54-7104/150Z/5000, 27-2064-3704/Z300, 27-2164-5710/Z300)

Ex db eb mb IIC T3 Gb (Ta: -20°C/-40°C~+55°C, Max. 250A)

(With heater:CREx02031.0-XX,CREx02032.0-XX, 27-2A53-7104/110Z/5000)

Ex tb IIIC T80°C Db (Ta: -20°C/-40°C~+45°C/+55°C) (with any one of the heater mentioned above.)

Note: protection type “mb” depends on the use of Ex component certified voltmeter or fuse.

List of the components covered by separated IECEx certificates and statement of the assessments regarding the older editions of the standards:

Components/ Equipment	Manufacturer	Model/Type	Certificate No.	Standard(s) and date(s)/edition(s)
Explosion-proof circuit breaker modules	Warom	BL8060-*/**/*/*/*/* BL8060-100/*/*/*	IECEX CQM 14.0031U	IEC 60079-0:2017; IEC 60079-1:2014; IEC 60079-7:2017



Attachment to CoC

IECEX CQM 22.0002X issue 5



Components/ Equipment	Manufacturer	Model/Type	Certificate No.	Standard(s) and date(s)/edition(s)
Explosion-proof circuit breaker modules	Warom	BL8060-d/□/□/□/□ /□	IECEX CQM 15.0016U	IEC 60079-0:2017; IEC 60079-1:2014
Explosion-proof Indicator	Warom	BD8060-/□/□/□	IECEX CQM 24.0019U	IEC 60079-0:2017 IEC 60079-1:2014 IEC 60079-7:2017
Explosion-proof Indicator lampshade	Warom	BD8160-□	IECEX CQM 24.0018U	IEC 60079-0:2017 IEC 60079-7:2017 IEC 60079-31:2022
Explosion-proof button operating device	Warom	BA8160-□	IECEX CQM 24.0017U	IEC 60079-0:2017 IEC 60079-7:2017 IEC 60079-31:2022
Convection type heater	STEGO FRANCE SAS	CREx02041.0-XX CREx02042.0-XX CREx02051.0-XX CREx02052.0-XX CREx02031.0-XX CREx02032.0-XX	IECEX EPS 16. 0048X	IEC 60079-0:2017; IEC 60079-1:2014; IEC 60079-31:2022
Temperature switch	STEGO France SAS	REx 011	IECEX EPS 16. 0054X	IEC 60079-0:2017; IEC 60079-1:2014; IEC 60079-31:2013 ¹⁾
Temperature switch	BARTEC GmbH	KTE-d	IECEX PTB 14.0016X	IEC 60079-0:2017; IEC 60079-1:2014; IEC 60079-31:2013 ¹⁾
Heater HS*	BARTEC GmbH	27-2C54-7054/110 Z/5000 27-2A53-7104/110 Z/5000 27-2B54-7104/150 Z/5000	IECEX PTB 14.0019X	IEC 60079-0:2017; IEC 60079-1:2014; IEC 60079-31:2013 ¹⁾
Heater HC*	BARTEC GmbH	27-2064-3704/Z300 27-2164-5710/Z300	IECEX PTB 14.0020X	IEC 60079-0:2017; IEC 60079-1:2014; IEC 60079-31:2013 ¹⁾
Explosion-proof Ammeters/Voltmeter	Warom	BB8050 Series	IECEX TPS 22.0022U	IEC 60079-0:2017 IEC 60079-7:2017 IEC 60079-18:2017
Explosion-proof control button	Warom	BA8060-/□/□	IECEX CQM 24.0016U	IEC 60079-0:2017 IEC 60079-1:2014 IEC 60079-7:2017
Explosion-proof control switch	Warom	BK8050-□	IECEX CQM 11.0011U	IEC 60079-0:2017 IEC 60079-1:2014 IEC 60079-7:2017
Modular terminal blocks	Weidmüller Interface GmbH & Co. KG	WPD 104	IECEX CNEX 16.0005U	IEC 60079-0:2017 IEC 60079-7:2017
Explosion-proof drain plug (breather)	Warom	BPS(H)-II	IECEX CQM 22.0023X	IEC 60079-0:2017 IEC 60079-1:2014 IEC 60079-7:2017 IEC 60079-31:2022



Attachment to CoC

IECEX CQM 22.0002X issue 5



Components/ Equipment	Manufacturer	Model/Type	Certificate No.	Standard(s) and date(s)/edition(s)
Explosion-proof Fuse	Warom	BRT8060-*	IECEX CQM 23.0002U	IEC 60079-0:2017 IEC 60079-7:2017 IEC 60079-18:2017
Explosion-proof box	Warom	BXC8060-□	IECEX CQM 24.0024U	IEC 60079-0:2017 IEC 60079-1:2014
Terminal blocks	PHOENIX CONTACT GmbH & Co. KG	UK *,UKH *	IECEX KEM 06.0034U IECEX KEM 06.0029U IECEX KEM 06.0030U IECEX SEV 12.0008U	IEC 60079-0:2017 IEC 60079-7:2017;
Terminal blocks	Weidmüller Interface GmbH & Co. KG	WDU*	IECEX ULD 14.0005U	IEC 60079-0:2017; IEC 60079-7:2017
Terminal blocks	Connectwell Industries Pvt Ltd	CTS*	IECEX SIR 20.0046U	IEC 60079-0:2017 IEC 60079-7:2017 IEC 60079-11:2011
Terminal blocks	Weidmüller Interface GmbH & Co. KG	SAKK series	IECEX TUR 18.0018U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	Weidmüller Interface GmbH & Co. KG	AKZ/AKE Series	IECEX TUR 18.0024U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	WAGO GmbH & Co. KG	279-***,280-***,281-***,282-***,283-***,284-***,285-(*)***	IECEX PTB 03.0004U IECEX PTB 14.0046U IECEX PTB 16.0001U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	PHOENIX CONTACT GmbH & Co. KG	MUT*	IECEX SEV 13.0012U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	PHOENIX CONTACT GmbH & Co. KG	PT*	IECEX SEV 13.0005U IECEX PTB 10.0021U IECEX PTB 10.0046U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	PHOENIX CONTACT GmbH & Co. KG	RBO*	IECEX SEV 13.0003U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	PHOENIX CONTACT GmbH & Co. KG	RT(O)*	IECEX PTB 08.0063U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	PHOENIX CONTACT GmbH & Co. KG	ST*	IECEX KEM 06.0051U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	PHOENIX CONTACT GmbH & Co. KG	UT*	IECEX KEM 06.0027U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	Weidmüller Interface GmbH & Co. KG	WDK*	IECEX ULD 15.0003U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	Weidmüller Interface GmbH & Co. KG	WFF*	IECEX ULD 15.0004U	IEC 60079-0:2017 IEC 60079-7:2017
Terminal blocks	Weidmüller	ZDU*	IECEX ULD 15.0008U	IEC 60079-0:2017



Attachment to CoC

IECEX CQM 22.0002X issue 5



Components/ Equipment	Manufacturer	Model/Type	Certificate No.	Standard(s) and date(s)/edition(s)
	Interface GmbH & Co. KG			IEC 60079-7:2017
Explosion-proof Plug and Socket	Warom	BCZ8060-16/□/□ BCZ8060-32/□/□	IECEX CNEX 21.0004X	IEC 60079-0:2017 IEC 60079-1:2014 IEC 60079-31:2022 IEC 60079-7:2017

Note 1: Not impacted by the major technical changes until the standard IEC 60079-31:2022