

Selection table

Rated voltage	Lamp	Lamp power (W)	Temperature classes			
			-40℃≤Ta≤+40℃		-40℃≤Ta≤+55℃	
			Gas	Dust	Gas	Dust
120V AC 50/60Hz	HIE	70, 100, 150	T4	T130℃	T4	T130℃
		175, 250, 400	T3	T195℃	T3	T195℃
	HSE	70, 100	T6	T80℃	T5	T95℃
		150, 250, 400	T3	T195℃	T3	T195℃
208V AC 50/60Hz	HIE	70, 100, 150	T5	T95℃	T4	T130℃
		175, 250, 400	T3	T195℃	T3	T195℃
	HME	80, 125	T5	T95℃	T4	T130℃
		250, 400	T3	T195℃	T3	T195℃
	HSE	70, 100	T6	T80℃	T5	T90℃
		150, 250, 400	T3	T195℃	T3	T195℃
220V AC 50/60Hz	HIE	175, 250, 400	T3	T195℃	T3	T195℃
	HME	250, 400	T3	T195℃	T3	T195℃
	HSE	150, 250, 400	T3	T195℃	T3	T195℃
230V AC 50/60Hz	HIE	70, 100, 150	T4	T130℃	T3	T195℃
		175, 250, 400	T3	T195℃	T3	T195℃
	HME	80, 125	T4	T130℃	T4	T130℃
		250	T4	T130℃	T3	T195℃
		400	T3	T195℃	213℃	T213℃
	HSE	70, 100, 150, 250	T4	T130℃	T4	T130℃
		400	T3	T195℃	211℃	T211℃
240V AC 50/60Hz	HIE	70, 100, 150	T4	T130℃	T4	T130℃
		175, 250, 400	T3	T195℃	T3	T195℃
	HME	80, 125, 250	T4	T130℃	T3	T195℃
		400	T3	T195℃	216℃	T216℃
	HSE	70, 100	T4	T130℃	T4	T130℃
		150, 250	T3	T195℃	T3	T195℃
		400			217℃	T217℃
250V AC 50/60Hz	HIE	70, 100, 150	T4	T130℃	T4	T130℃
		175, 250, 400	T3	T195℃	T3	T195℃
	HME	80, 125	T5	T95℃	T4	T130℃
		250	T4	T130℃	T3	T195℃
		400	T3	T195℃	221℃	T221℃
	HSE	70, 100	T5	T95℃	T4	T130℃
		150, 250	T3	T195℃	T3	T195℃
		400	211℃	T211℃	231℃	T231℃
277V AC 50/60Hz	HIE	70, 100, 150	T5	T95℃	T4	T130℃
		175, 250	T4	T130℃	T3	T195℃
		400	T3	T195℃	213℃	T213℃
	HME	80, 125	T5	T95℃	T4	T130℃
		250	T3	T195℃	T3	T195℃
	HSE	70, 100	T4	T130℃	T4	T130℃
		150, 250	T3	T195℃	T3	T195℃
		400	210℃	T210℃	230℃	T230℃