



Selection table

Version	Internal nominal diameter (mm)	Pipe connector thread "H"			Length L (mm)	Minimum bending radius (mm)	Ordering code	Weight (kg)
		Metric	NPT	G				
 <p>BNG-□x□□(M)/□□(F)</p>	13	M20	1/2"	1/2"	700	80	712001	0.55
	13	M20	1/2"	1/2"	1000	80	712002	0.70
	15	M25	3/4"	3/4"	700	110	712003	0.85
	15	M25	3/4"	3/4"	1000	110	712004	1.00
	18	M32	1"	1"	700	145	712005	1.05
	18	M32	1"	1"	1000	145	712006	1.15
	25	M40	1 1/4"	1 1/4"	700	180	712007	1.25
	25	M40	1 1/4"	1 1/4"	1000	180	712008	1.30
	30	M50	1 1/2"	1 1/2"	700	210	712009	1.70
	30	M50	1 1/2"	1 1/2"	1000	210	712010	1.95
 <p>BNG-□x□□(M)/□□(M)</p>	47	M63	2"	2"	700	250	712011	2.35
	47	M63	2"	2"	1000	250	712012	2.40
	13	M20	1/2"	1/2"	700	80	712013	0.50
	13	M20	1/2"	1/2"	1000	80	712014	0.65
	15	M25	3/4"	3/4"	700	110	712015	0.80
	15	M25	3/4"	3/4"	1000	110	712016	0.95
	18	M32	1"	1"	700	145	712017	1.00
	18	M32	1"	1"	1000	145	712018	1.05
	25	M40	1 1/4"	1 1/4"	700	180	712019	1.15
	25	M40	1 1/4"	1 1/4"	1000	180	712020	1.20
 <p>BNG-□x□□(F)/□□(F)</p>	30	M50	1 1/2"	1 1/2"	700	210	712021	1.60
	30	M50	1 1/2"	1 1/2"	1000	210	712022	1.80
	47	M63	2"	2"	700	250	712023	2.15
	47	M63	2"	2"	1000	250	712024	2.25
	13	M20	1/2"	1/2"	700	80	712025	0.65
	13	M20	1/2"	1/2"	1000	80	712026	0.75
	15	M25	3/4"	3/4"	700	110	712027	0.95
	15	M25	3/4"	3/4"	1000	110	712028	1.05
	18	M32	1"	1"	700	145	712029	1.10
	18	M32	1"	1"	1000	145	712030	1.30
	25	M40	1 1/4"	1 1/4"	700	180	712031	1.35
	25	M40	1 1/4"	1 1/4"	1000	180	712032	1.40
	30	M50	1 1/2"	1 1/2"	700	210	712033	1.80
	30	M50	1 1/2"	1 1/2"	1000	210	712034	2.15
	47	M63	2"	2"	700	250	712035	2.55
	47	M63	2"	2"	1000	250	712036	3.15