

Selection table of cable wiring													
Gland size	Entry thread "A"		Cable outer diameter B (mm)		Cable outer diameter C (mm)		Minimum thread length D (mm)	Nominal protrusion length E (mm)	Across corners G (mm)	Armour/Braid(h)		Ordering code	Weight (kg)
	Metric	NPT/G	Min	Max	Min	Max				X	W		
20A	M20	1/2"	4.0	8.0	5.5	12.0	15	59	31	0~0.6	0.8~1.4	722001	0.12
20B	M20	1/2"	6.5	10.5	9.0	16.0	15	59	31	0~0.6	0.8~1.4	722002	0.15
20C	M20	1/2"	8.5	14.5	12.5	20.5	15	61	37	0~0.6	0.8~1.4	722003	0.15
25B	M25	3/4"	8.5	14.5	12.5	20.5	15	61	37	0~0.6	0.8~1.4	722004	0.19
25C	M25	3/4"	11.0	19.5	17.0	26.0	15	65	45	0~0.7	1.0~1.7	722005	0.18
32B	M32	1"	11.0	19.5	17.0	26.0	15	65	45	0~0.7	1.0~1.7	722006	0.22
32C	M32	1"	17.0	25.5	22.0	33.0	15	70	54	0~0.8	1.0~1.7	722007	0.30
40B	M40	1 1/4"	17.0	25.5	22.0	33.0	19	70	54	0~0.8	1.0~1.7	722008	0.40
40C	M40	1 1/4"	23.0	32.0	28.0	41.0	19	78	65	0~1.0	1.0~2.0	722009	0.40
50B	M50	1 1/2"	23.0	32.0	28.0	41.0	19	78	65	0~1.0	1.0~2.0	722010	0.60
50C	M50	1 1/2"	29.0	39.0	36.0	52.5	19	90	77	0~1.0	1.0~2.0	722011	0.80
63B	M63	2"	29.0	39.0	36.0	52.5	19	90	77	0~1.0	1.0~2.0	722012	1.00
63C	M63	2"	42.0	50.0	46.0	65.0	19	115	93	0~1.2	1.5~2.7	722013	1.20
75B	M75	2 1/2"	42.0	50.0	46.0	65.0	19	115	93	0~1.2	1.5~2.7	722014	1.20
75C	M75	2 1/2"	48.0	60.0	57.0	78.0	19	125	110	0~1.5	2.0~3.5	722015	1.30

Selection table of steel pipe wiring															
Gland size	Entry thread "A"		Entry thread "H"		Cable outer diameter B (mm)		Cable outer diameter C (mm)		Minimum thread length D (mm)	Nominal protrusion length E (mm)	Across corners G (mm)	Armour/Braid(h)		Ordering code	Weight (kg)
	Metric	NPT/G	Metric	NPT/G	Min	Max	Min	Max				X	W		
20A	M20	1/2"	M20	1/2"	4.0	8.0	5.5	12.0	15	74	31	0~0.6	0.8~1.4	722024	0.15
20B	M20	1/2"	M20	1/2"	6.5	10.5	9.0	16.0	15	74	31	0~0.6	0.8~1.4	722025	0.20
20C	M20	1/2"	M25	3/4"	8.5	14.5	12.5	20.5	15	76	37	0~0.6	0.8~1.4	722026	0.20
25B	M25	3/4"	M25	3/4"	8.5	14.5	12.5	20.5	15	76	37	0~0.6	0.8~1.4	722027	0.24
25C	M25	3/4"	M32	1"	11.0	19.5	17.0	26.0	15	84	45	0~0.7	1.0~1.7	722028	0.27
32B	M32	1"	M32	1"	11.0	19.5	17.0	26.0	15	84	45	0~0.7	1.0~1.7	722029	0.27
32C	M32	1"	M40	1 1/4"	17.0	25.5	22.0	33.0	15	89	54	0~0.8	1.0~1.7	722030	0.33
40B	M40	1 1/4"	M40	1 1/4"	17.0	25.5	22.0	33.0	19	89	54	0~0.8	1.0~1.7	722031	0.36
40C	M40	1 1/4"	M50	1 1/2"	23.0	32.0	28.0	41.0	19	97	65	0~1.0	1.0~2.0	722032	0.45
50B	M50	1 1/2"	M50	1 1/2"	23.0	32.0	28.0	41.0	19	97	65	0~1.0	1.0~2.0	722033	0.70
50C	M50	1 1/2"	M63	2"	29.0	39.0	36.0	52.5	19	109	77	0~1.0	1.0~2.0	722034	0.85
63B	M63	2"	M63	2"	29.0	39.0	36.0	52.5	19	109	77	0~1.0	1.0~2.0	722035	1.50
63C	M63	2"	M75	2 1/2"	42.0	50.0	46.0	65.0	19	134	93	0~1.2	1.5~2.7	722036	1.70
75B	M75	2 1/2"	M75	2 1/2"	42.0	50.0	46.0	65.0	19	134	93	0~1.2	1.5~2.7	722037	1.70
75C	M75	2 1/2"	M90	3"	48.0	60.0	57.0	78.0	19	144	110	0~1.5	2.0~3.5	722038	1.80

Note: 1. Standard material is nickel plated brass. Stainless steel is optional. Above weight is based upon nickel plated brass.
2. Earth lug and shroud on request. See P7/38~39.
3. Metric threads are 1.5mm pitch as standard, others thread pitch can be customized, please specify when ordering.