

Selection table of cable wiring											
Gland size	Entry thread "A"		Cable outer diameter B (mm)				Minimum thread length C (mm)	Nominal protrusion length D (mm)	Across corners F (mm)	Ordering code	Weight (kg)
			Standard Seal		Alternative Seal						
	Metric	NPT/G	Min	Max	Min	Max					
20A	M20A	1/2"A	6.5	10.5	4	8	15	33	31	708001	0.15
20B	M20B	1/2"B	10	14.5	8	12	15	38	31	708002	0.15
25	M25	3/4"	14.5	19.5	11	15.5	15	42	37	708003	0.20
32	M32	1"	19	25.5	17	21.5	15	44	45	708004	0.30
40	M40	1 1/4"	25	32	22	28	19	47	54	708005	0.45
50	M50	1 1/2"	31.5	39	27.5	35	19	49	65	708006	0.70
63	M63	2"	40	50	35	42	19	61	77	708007	0.90
75	M75	2 1/2"	54.5	NPT: 60.0	48.5	58	19	66	93	708008	2.30
				M/G: 64.0							
90	M90	3"	63	75	-	-	19	69	110	708009	2.50
115	M115	4"	75	90	-	-	19	75	137	708010	4.60
Selection table of steel pipe wiring											
Gland size	Entry thread "A"		Entry thread "H"		Cable outer diameter B (mm)		Minimum thread length C (mm)	Nominal protrusion length D (mm)	Across corners F (mm)	Ordering code	Weight (kg)
	Metric	NPT/G	Metric	NPT/G	Min	Max					
20A	M20A	1/2"A	M20	1/2"	8	12	15	40	34	708011	0.20
20B	M20B	1/2"B	M20	1/2"	10	14.5	15	40	34	708012	0.20
25A	M25A	3/4"A	M25	3/4"	11	15.5	15	40	42	708013	0.25
25B	M25B	3/4"B	M25	3/4"	14.5	19.5	15	40	42	708014	0.25
32A	M32A	1"A	M32	1"	17	21.5	15	45	48	708015	0.40
32B	M32B	1"B	M32	1"	19	25.5	15	45	48	708016	0.40
40	M40	1 1/4"	M40	1 1/4"	20	30	19	58	65	708017	0.60
50	M50	1 1/2"	M50	1 1/2"	26	37	19	58	75	708018	0.75
63	M63	2"	M63	2"	30	47	19	65	87	708019	1.15
75	M75	2 1/2"	M75	2 1/2"	38	57	19	65	110	708020	1.50
90	M90	3"	M90	3"	55	67	19	65	115	708021	1.80
115	M115	4"	M115	4"	48	80	19	69	145	708022	3.50
<b>Note:</b> 1. Standard material is nickel plated brass. Stainless steel is optional. Above weight is based upon nickel plated brass. 2. Earth lug and shroud on request. See P7/38~39. 3. Metric threads are 1.5mm pitch as standard, others thread pitch can be customized, please specify when ordering.											