

Selection table of cable wiring										
Gland size	Entry thread "A"		Cable outer diameter B (mm)	Cable outer diameter C (mm)		Minimum thread length D (mm)	Nominal protrusion length E (mm)	Across corners G (mm)	Ordering code	Weight (kg)
	Metric	NPT/G	Max	Min	Max					
20A	M20A	1/2"A	10	5.5	12	15	51	31	710001	0.10
20B	M20B	1/2"B	13	9.0	16	15	51	31	710002	0.10
25A	M25A	3/4"A	13	9.0	16	15	51	37	710003	0.12
25B	M25B	3/4"B	18	12.5	20.5	15	53	37	710004	0.15
32A	M32A	1"A	18	12.5	20.5	15	53	45	710005	0.17
32B	M32B	1"B	24	17	26	15	58	45	710006	0.20
40A	M40A	1 1/4"A	24	17	26	19	58	54	710007	0.22
40B	M40B	1 1/4"B	30	22	33	19	62	54	710008	0.27
50A	M50A	1 1/2"A	30	22	33	19	62	65	710009	0.40
50B	M50B	1 1/2"B	37	28	41	19	69	65	710010	0.50
63A	M63A	2"A	37	28	41	19	69	77	710011	0.80
63B	M63B	2"B	47	36	52.5	19	77	77	710012	0.90
75A	M75A	2 1/2"A	47	36	52.5	19	77	90	710013	2.30
75B	M75B	2 1/2"B	55	46	65	19	95	110	710014	2.70
90	M90	3"	60	57	78	19	100	121	710015	2.80
115	M115	4"	70	68	88	19	106	137	710016	3.60

Selection table of steel pipe wiring												
Gland size	Entry thread "A"		Entry thread "H"		Cable outer diameter B (mm)	Cable outer diameter C (mm)		Minimum thread length D (mm)	Nominal protrusion length E (mm)	Across corners G (mm)	Ordering code	Weight (kg)
	Metric	NPT/G	Metric	NPT/G	Max	Min	Max					
20A	M20A	1/2"A	M20	1/2"	10	5.5	12	15	66	31	710017	0.12
20B	M20B	1/2"B	M20	1/2"	13	9.0	16	15	66	31	710018	0.12
25A	M25A	3/4"A	M20	1/2"	13	9.0	16	15	66	37	710019	0.15
25B	M25B	3/4"B	M25	3/4"	18	12.5	20.5	15	68	37	710020	0.18
32A	M32A	1"A	M25	3/4"	18	12.5	20.5	15	68	45	710021	0.21
32B	M32B	1"B	M32	1"	24	17	26	15	77	45	710022	0.24
40A	M40A	1 1/4"A	M32	1"	24	17	26	19	77	54	710023	0.29
40B	M40B	1 1/4"B	M40	1 1/4"	30	22	33	19	81	54	710024	0.35
50A	M50A	1 1/2"A	M40	1 1/4"	30	22	33	19	81	65	710025	0.50
50B	M50B	1 1/2"B	M50	1 1/2"	37	28	41	19	88	65	710026	0.64
63A	M63A	2"A	M50	1 1/2"	37	28	41	19	88	77	710027	0.98
63B	M63B	2"B	M63	2"	47	36	52.5	19	96	77	710028	1.17
75A	M75A	2 1/2"A	M63	2"	47	36	52.5	19	96	90	710029	2.60
75B	M75B	2 1/2"B	M75	2 1/2"	55	46	65	19	114	110	710030	3.00
90	M90	3"	M90	3"	60	57	78	19	119	121	710031	3.30
115	M115	4"	M115	4"	70	68	88	19	125	137	710032	4.00

Note: 1. Standard material is nickel plated brass. Stainless steel is optional. Above weight is based upon nickel plated brass.
2. Earth lug and shroud on request. See P7/38~39.
3. Metric threads are 1.5mm pitch as standard, others thread pitch can be customized, please specify when ordering.