

CBY20-L LED角灯

CBY20-L
LED Corner Lamp



应用场所 Application

- 适用于居所，通道及相应区域。
- Accommodations, passage and corresponding area.

型号含义 Catalogue number logic



CBY20-L LED角灯

CBY20-L LED Corner Lamp

灯体 Housing

- 优质钢板，表面喷白色塑粉
- High-quality steel plate with white plastic powder sprayed on the surface

透明罩 Transparent cover

- 乳白色PC材质
- Milk white PC material

电气 Electric

- 恒流恒压驱动电源
- Constant current constant voltage driving power

安装方式 Mounting

- 使用4个 $\Phi 6 \times 14$ mm的安装孔位来固定
- Fix by means of $4 \times \Phi 6 \times 14$ mm mounting holes

可选配件 Options

- E 集中电源应急
- LEDT : LED灯管(T5)
- E Centralized power supply for emergency
- LEDT: LED Tube (T5)

选配表 Selection table

型号 Type	额定电压(V) Rated voltage	光源类型 Light source	额定功率(W) Rated power	重量(kg) Weight
CBY20-L	220V~240V AC 50/60Hz 110V/120V AC 60Hz	LED 模组 LED module	9W×1	3.3

- E: 集中电源应急(DC24V/3W) Centralized power supply for emergency

技术参数 Technical parameters

执行标准 Conformity to standards	IEC 60598 , IEC 60092-306 , CCS 入级规范 (CCS standard)
环境温度 Ambient temperature	-40°C~+55°C
防护等级 Degree of protection	IP44
光源类型 Light source	LED 模组 LED module
色温 Color temperature	5000K±250K (3000K、4000K可选 Optional)
显色指数 Color rendering index	Ra≥80
电缆引入口 Cable entris	20×50孔，适用于 $\Phi 11 \sim \Phi 13$ mm电缆 20×50 Hole, suitable for $\Phi 11 \sim \Phi 13$ mm cable
接线端子 Terminal	1.5~4mm ²

外形尺寸 Outline dimension

