

## FZA 系列防水防尘防腐主令电器

### FZA Series Weatherproof Control Unit Systems



#### 型号规格含义 Nomenclature



#### 订货须知 Ordering Information

- ◆ 二钮一灯，2个按钮规格均为一常开一常闭标准型绿色按钮，指示灯为220V红色1个。  
标注为：FZA-A2D1  
A2-2 III a2  
D1-1Rf
- ◆ Two buttons and one light, the buttons shall be 1 NO+ 1NC type standard green button, the indicator is red and of 220V.  
The product should be marked with: FZA- A2D1  
A2-2 III a2  
D1-1Rf

### 技术参数 Technical Parameters

执行标准 Executive standards	中国GB标准 Chinese GB standards	欧盟EN标准 European EN standards
额定电压 Rated voltage	220V/380V、230V/400V	Max.440V AC 50/60Hz Max. 250V DC
额定电流 Rated current	3A(16A 可选 Optional)	
环境温度 Ambient temperature	-40°C ~ +55°C	
防护等级 Degree of protection	IP65/IP66(可选 Optional)	
进线口螺纹 Thread for inlet and outlet	PG16引入口规格 (M20×1.5可选) Thread for inlet and outlet: PG16 Cable entry (M20×1.5 Optional)	
电缆外径 Cable outer diameter	适合Φ8.5mm~Φ14mm电缆 Suitable for cable of Φ8.5mm~Φ14mm	
壳体材质 Enclosure material	工程塑料 Engineering plastics	

### 外形尺寸 Outline dimension

